

H 96071

# Anschlussmanschette NW 20, mit Schrumpfschlauch

<b>Product</b>	Connection collar for the pass through of pipes, cables, conductions, fixings etc. at roof and basement waterproofings
<b>Application</b>	Torch-on method. The upper end is covered against water with the enclosed shrink tube.
<b>Remarks</b>	Further dimensions on request.

<b>Characteristics</b>	<b>Unit</b>	<b>Result</b>
Height	mm	300
Inside diameter	mm	20
Outside diameter	mm	26
Collar diameter	mm	430
Shrink tube length	mm	ca. 200
Shrink tube diameter	mm	28/6
shrinkable to	mm	6

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

**Subject to alteration without notice.**

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

**Development, Production and Sales of our products according to ISO 9001.**